

# Pioneer All-in-One (SL15)



The Pioneer All-in-One terminal is a compact system consisting of a rugged 15" touchscreen and fully integrated Epson thermal receipt printer. The terminal is simple to set up and reduces cable clutter.



## Point of Sale System

### Technical Specifications

<b>Display Size</b>	15" 1024 x 768
<b>Spill Proof</b>	IP65 Rated Front Panel Only
<b>Operating System</b>	Linux
<b>Network/Ethernet</b>	Wired Network via Ethernet
<b>Connectivities</b>	5X USB 2.0/Core: 2X USB 2.0, 3X USB 3.0
<b>Dimensions</b>	16.3 x 15 x 13
<b>Weight</b>	26 lbs
<b>Mounting Options</b>	Desktop Sline Base (Epson printer built-in) or no printer for desktop or wall mounting
<b>Operating Environment</b>	0°C to 40°C, 20% to 80% Humidity
<b>Warranty</b>	3 Years
<b>Optional External Peripherals</b>	RFID or barcode readers

# Alfred AD-215 Self-Service Kiosk



The Alfred self-service kiosk features a 21.5" touchscreen, built-in thermal printer, and 2D barcode scanner. With flexible mounting options and modern design, this kiosk will fit in any setting.



## Technical Specifications

<b>Item</b>	AD-215 (Linux)
<b>Display</b>	21.5", 16:9, 1920 x 1080(300 nits)
<b>I/O Ports</b>	1 x Intel LAN (IEEE 802.3 10/100/1000 (Mbps)) 4 x USB 3.2 + 2 x USB 2.0   3 x USB 3.2 + 3 x USB 2.0
<b>Printer</b>	3" thermal printer
<b>Barcode Scanner</b>	2D barcode scanner
<b>Peripheral Options</b>	MSR, EMV terminal brackets for supported credit card terminals
<b>Mounting Options</b>	Desktop stand, floor stand or wall mount (standard VESA)
<b>Wi-Fi</b>	Wi-Fi Option Available
<b>Reliability</b>	System operating temperature: 0 ~ 40°C / 32 ~ 104°F System humidity: 15% ~ 80% Storage temperature: -20 ~ 60°C / -4 ~ 140°F
<b>Dimensions</b>	<p><b>Floor Stand</b> Landscape: 524 x 1482 x 401 mm / 20.6 x 15.8 in (<b>AD-215</b>) Portrait: 380 x 1572 x 401 mm / 15 x 61.9 x 15.8 in (<b>AD-215</b>)</p> <p><b>Desktop Stand</b> Landscape: 524 x 728 x 324 mm / 20.6 x 28.7 x 12.8 in (<b>AD-215</b>) Portrait: 324 x 818 x 324 mm / 12.8 x 32.2 x 12.8 in (<b>AD-215</b>)</p>

# Cleo C14 Terminal



The Cleo C14 is an all-in-one POS terminal with a 14.1" touchscreen and built-in thermal printer. The compact design makes this an ideal solution for areas with limited counter space. The spill-proof display and solid-drive make this unit resistant to dust, shocks, and vibrations.



<b>Screen Size/ Resolution</b>	<b>C10-1E &amp; C14-1E (Elkhart Lake):</b> C14: 14.1" (1366 x 768, 220 nits)
<b>Aspect Ratio</b>	16:9
<b>Touch</b>	PCAP touch
<b>External I/O Interface</b>	4 x USB 3.2 + 2 x USB 2.0 1 x LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) 1 x DC +24V input
<b>Printer</b>	3" Thermal printer
<b>Power Adapter</b>	Input: 100 ~ 240V / Output 24V, 72W
<b>Reliability</b>	System operating temperature: 0 ~ 104°F / 0 ~ 40°C System humidity: 15% ~ 80% Storage temperature: -4 ~ 140°F / -20 ~ 60°C
<b>Dimensions</b>	<b>C14:</b> 13.41" (W) x 12.41" (H) x 9.73" (D) / 341 mm (W) x 315 mm (H) x 247.13 (D)
<b>Weight</b>	<b>C14:</b> 8.82 lbs / 4 kg

# M3W-2 Rugged Tablet



The M3w-2 Enterprise Tablet offers a powerful mobile POS technology designed especially for retail and hospitality environments.



## POS Base Adds Utility

While the M3w-2 works well as a mobile, handheld device, its POS base options give it the flexibility to be a countertop POS terminal. Base options have multiple I/O ports for connection to a printer, cash drawer, Ethernet. A key lock secures the tablet in place.

## Special Features

- Wireless communication capabilities
- Easy all-day use for indoor and outdoor

## Built Tough for Busy Environments

This tablet is ready for the most demanding environments. It has an IP54 sealing rating, which means it is highly resistant to dust and moisture, including spills that sometime occur in busy retail stores or restaurant.

## Optional

- POS Base
- Battery Charging Cradle
- Built-in Barcode Scanner
- MSR Scanner

# M3W-2

## Spec Sheet



<b>Display</b>	10.1" 16:10 1280 x 800 350nits
<b>I/O Interface</b>	1 x Type ~ A USB 3.0 1 x Micro B USB 2.0 1 x DC Jack 1 x POGO Pins
<b>Battery</b>	Main Battery: 7.4V, 4600mAH Swappable battery: 3.8V / 250 mAH
<b>Peripheral Options</b>	RFID 2D barcode scanner POS Base, Battery Charging cradle
<b>Network</b>	Wired Network via Ethernet with Dock Wireless Capable
<b>Drop</b>	3ft (Meter)
<b>Spill &amp; Dust Resistant</b>	IP54 Certified
<b>Operation System</b>	Linux
<b>Printer</b>	3" Thermal printer
<b>Reliability</b>	System operating temperature: 0 ~ 40°C / 32 ~ 104°F System humidity: 15% ~ 80% Storage temperature: -20 ~ 60°C / -4 ~ 140°F
<b>Dimensions (W x H x D)</b>	278 x 199 x 24.2 mm / 10.95 x 7.83 x 0.95 in
<b>Weight</b>	1.1 Kgs / 2.43 lb



# POS Base M3W-2

## Specifications

Item	X3-10
<b>Mechanism</b>	POS Base Mini
<b>USB</b>	4
<b>COM</b>	4
<b>Ethernet</b>	1
<b>Cash Drawer</b>	1
<b>DC</b>	12V 7.5A 90W
<b>Dimensions (W x H x D) mm</b>	278*225.25*321.1

